

Simulated Meeting Rail (SMR) Option

CASEMENT AND AWNING WINDOWS

NEW DOUBLE HUNG LOOK FOR 2012!



Looks like a Double Hung. Performs like a Casement.

This new option provides higher structural performance levels than a traditional double hung, with the ability to meet egress requirements in smaller unit sizes. It reduces the need for a complete tear out, and provides more daylight by utilizing our new Casement design. All these great features of a Casement or Awning window, while keeping the look of a Double Hung or Sliding Window.

KEY FEATURES

- ▶ **Greater range of egress compliance** over a double hung or traditional vinyl casement designs. Typical building code requirements are 5.7 sq. ft. of opening, with a minimum opening width of 20" and minimum opening height of 24".
 - Our new casement with optional egress hinge option meets all of these requirements in a unit size of 26 5/8" x 45 15/16" tall (1 3/16" narrower than a traditional vinyl casement). Also, it's smaller than our 28" x 82 1/4" compliant Double Hung window.
 - Ability to meet code without requiring a complete tear out or sacrificing the traditional look of a Double Hung.
- ▶ **High wind zone compliant** - Our casement window has been tested and meets the requirements for a PG70 (24" x 60" test size) overall performance rating, which is equivalent to a 165 MPH wind speed.
 - Air infiltration rate of 0.01, one of the lowest available, reduces the heating and cooling costs of your home.
 - The harder the wind blows, the tighter the window seals, protecting against unwanted drafts.

Design Options



Grid Types



Standard

V-Groove



Georgian

Simulated Divided Lites

Optional Architectural Hardware



Oil rubbed bronze



Brushed nickel



Antique brass



SUNRISE WINDOWS
The Difference is Clear!™